INDEX OF SHEETS

SHE	ET NO.	DESCRIPTION
	1	TITLE SHEET
	2	INDEX OF SHEETS, STATE STANDARDS & GENERAL NOTES.
	3	SUMMARY OF QUANTITIES
	4-5	EXISTING AND PROPOSED TYPICAL SECTIONS
	6-8	ROADWAY AND PAVEMENT MARKING PLANS
	9-11	DETECTOR LOOP REPLACEMENT
	12	DETAILS FOR FRAMES AND LIDS ADJUSTMENT WITH MILLING
	13	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT
	14	CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT
	15	BUTT JOINT AND HMA TAPER DETAILS
	16	HMA TAPER AT EDGE OF PCC PAVEMENT
	17	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS AND DRIVEWAYS
	18	TYPICAL APPLICATIONS: RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)
	19	DISTRICT ONE TYPICAL PAVEMENT MARKINGS
	20	TRAFFIC CONTROL AND PROTECTION OF TURN BAYS (TO REMAIN OPEN TO TRAFFIC)
	21	PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING
	22	ARTERIAL ROAD INFORMATION SIGN

STATE STANDARDS

	STANDARD NO.	DESCRIPTION
	442201- 03	CLASS C AND D PATCHES
ŧ.	701301- <i>0</i> 3	LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS
	701501 <i>-05</i>	URBAN LANE CLOSURE, 2L, 2W, UNDIVIDED
	701606 - 06	URBAN LANE CLOSURE, MULTILANE, 2W WITH MOUNTABLE MEDIAN
1	701701 - 00	JURBAN LANE CLOSURE, MULTILANE INTERSECTION
	701901 - 01	TRAFFIC CONTROL DEVICES
		化二氢甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基

GENERAL NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT (800) 892-0123 OR 811 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE, AND GAS FACILITIES. (48 HOUR NOTIFICATION REQUIRED)

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES AND THE VILLAGE OF HOMEWOOD.

THE CONTRACTOR WILL NOT BE ABLE TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT THE WRITTEN PERMISSION OF THE DEPARTMENT.

BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT) IN ACCORDANCE WITH THE "BUTT JOINT AND HMA "APER DETAILS" SHEET INCLUDED IN THE PLANS UNLESS OTHERWISE SPECIFIED.

THE RESIDENT ENGINEER SHALL CONTACT MS. PATRICE HARRIS, AREA TRAFFIC FIELD ENGINEER, AT (708) 597-9800 A MINIMUM OF TWO WEEKS PRIOR TO PLACEMENT OF FINAL PAVEMENT MARKINGS.

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC, THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1 1/2 INCHES WHERE THE SPEED LIMIT IS 45 MPH OR LESS, AND 1 INCH WHERE THE SPEED LIMIT IS 45 MPH. WITH WRITTEN APPROVAL FROM THE RESIDENT ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM OF 1:3 (V:H)

THE CONTRACTOR SHALL CONTACT THE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM OF 72 HOURS IN ADVANCE OF BEGINNING WORK.

ANY PAVEMENT MARKING; AND RAISED REFLECTIVE PAVEMENT MARKERS
OBLITERATED BY MILLING AND RESURFACING OPERATIONS ON SIDE STREETS
AND ENTRANCES SHALL BE REPLACED AND PAID FOR IN KIND

ALL DAMAGE TO EXISTING PAVEMENT MARKINGS OR RAISED REFLECTIVE PAVEMENT MARKERS OUTSIDE THE REMOVAL LINE SHOWN ON THE PLANS SHALL BE REPLACED AT NO ADDITIONAL COST TO THE DEPARTMENT.

BEFORE BEGINNING ANY WORK, THE CONTRACTOR SHALL RETAIN AND RECORD FOR FUTURE REFERENCE, ALL EXISTING PAVEMENT MARKING LINES (AND RAISED REFLECTIVE PAVEMENT MARKERS) IN ORDER THAT THESE LOCATIONS CAN BE RE-ESTABLISHED FOR STRIPING. EXACT LOCATIONS OF ALL PAVEMENT MARKINGS SHALL BE AS DIRECTED BY THE ENGINEER.

ALL PAVEMENT PATCHING LOCATIONS WILL BE DETERMINED IN THE FIELD BY THE ENGINEER.

DRAINAGE ADJUSTMENT OR RECONSTRUCTION LOCATIONS WILL BE DETERMINED IN THE FIELD BY THE ENGINEER.

IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO VERIFY ALL DIMENSIONS AND CONDITIONS EXISTING IN THE FIELD PRIOR TO CONSTRUCTION AND ORDERING OF MATERIALS.

THE CONTRACTOR SHALL BE REQUIRED TO PROVIDE ACCESS TO ABUTTING PROPERTY AT ALL TIMES DURING THE CONSTRUCTION OF THIS PROJECT.

DO NOT SCALE PLANS FOR CONSTRUCTION DIMENSIONS.

DOUBLE LANE MARKERS ARE TO BE USED AS SHOWN ON THE DISTRICT ONE DETAIL "TYPICAL APPLICATIONS - RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)" SHOWN IN THE PLANS.

PAVEMENT MARKING TAPE, TYPE III SHALL BE USED FOR SHORT TERM PAVEMENT MARKINGS ON ALL FINAL SURFACES. THE COST OF THE PAVEMENT MARKING TAPE, TYPE III AND ITS REMOVAL SHALL BE INCLUDED IN THE COST OF SHORT TERM PAVEMENT MARKING.

1			
FILE NAME =	USER NAME = midyja	DESIGNED -	REVISED -
c:\pw_work\PWIBOT\MIDYJA\dms92647\sh_rd	wy.dgn	DRAWN -	REVISED -
	PLOT SCALE = 50,0000 '/ IN.	CHECKED -	REVISED -
1	PLOT DATE = 2/4/2009	DATE -	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

	DIXIE HIGHWAY								
	INDEX	0F	SHEETS,	STATE	STANDA	RDS AND	GENERAL NOTES		
SCALE:			SHEET NO.	OF	SHEETS	STA.	TO STA.		

 CCD D	DAD DIST. NO. 1 ILLINOIS FED. A			
		CONTRACT	NO. (SOB57
2843	2006-022 RS	COOK	22	2
F.A.U. RTE.	SECTION	COUNTY	TOTAL	SHEET NO.